

Software version		Category		Description	Note
RC9 controller	WINCAPSIII				
1.03.0	3.60.3			First edition.	
1.1.0	3.61.1	Function	Add	Added the brake check function.	
		Function	Add	Added the torque check function.	
		Function	Add	Supported the wall-mount and the tilted surface-mount.	
		PCS command	Change	Added Static option to Rotate command.	
		Function	Change	Improved the error recovery processing message.	
		Function	Add	Supported the PLC HMI Web.	
		Function	Add	Added the joint motion direction display at VM robot start-up.	
		Function	Add	Added Programmer (restricted) to the user level.	
		Function	Change	Changed the maximum value of the auto logout time.	
		Function	Add	Added the name setting and name display of the robot controller.	
		Function	Add	Added the virtual fence monitoring processing.	
		Function	Add	Added the extended-joint function.	
		Function	Add	Added the b-CAP Slave function.	
		Function	Add	WINCAPSIII: Added the virtual fence creation function.	
		Function	Add	WINCAPSIII: Added the supported model (VLA6022).	
1.2.1	3.62.0	Function	Add	Added the robot motion control function that is used through TwinCAT3.	
		Function	Add	Added the robot motion monitoring function that is used through TwinCAT3.	
		Function	Add	Added the external TCP function.	
		Function	Add	Supported MC9.	
		Function	Add	Expanded the virtual fence function to traveling shafts.	
		Function	Change	Improved the date and time setting function.	
		Function	Add	Added the Ping function.	
		Function	Change	Improved PanelDesigner.	
		Function	Add	WINCAPS3 : Added EVP2 program templates.	
		Function	Add	WINCAPS3 : Added the RC9 model data transfer function.	
		Function	Add	WINCAPS3 : Added the RC9 external TCP function.	
		Function	Add	WINCAPS3 : Added the supported model (MC9).	
		Function	Add	WINCAPS3 : Added the RC9 kinematics tool.	

Software version		Category		Description	Note
RC9 controller	WINCAPSIII				
1.3.0	3.63.0	Function	Add	Added the World coordinate system.	
		Function	Add	Added the External force following control function.	
		Function	Add	Added the Current limiting function.	
		Function	Change	Changed the VL initial setting procedures.	
1.9.2	3.66.0	Function	Add	Added the Free Curve Interpolation motion.	
		Function	Add	Added the RC9 project comparison feature.	
		Function	Change	In CC-Link, "2.0(Ver1.1 compatible)" became available.	
		Function	Change	Changed the maximum value of the EthernetIP input/output size.	
		Function	Change	In PROFINET, a 256Byte module became available.	
		Function	Change	Changed the function name "Master/Slave" to Mirror Control.	
		Function	Change	Changed the Smart TP UI.	
		Function	Change	A user account password is used as an XAE one-time password.	
		Function	Change	Changed the processing to be executed when the VLA is turned on for the first time.	
		Function	Change	Eliminated a communication error that occurs when setting the brightness on Smart TP.	
		Function	Change	Changed the items displayed in PanelDesigner.	
		Function	Change	Changed the Easy Setting screen.	
		Function	Change	Made the Payload Estimation function available only in Auto mode.	
		Function	Change	Made Auto Gain Tuning available only in Auto mode.	